

Version	Code	Item
Made of metal, with female 1/4" port (economic model)	572384	AH13
Made of plastic, with female 1/4" port and short nozzle	570167	AN13
Made of plastic, with female 1/4" port and extension tube	570166	AK13
Made of plastic, with female 1/4" port and female connection for accessories	570168	AM13
Silenced nozzle (for the blow gun type AM13)	570169	AR12
Venturi nozzle (for the blow gun type AM13)	570170	AT12
150 mm extension tube (for the blow gun type AM13)	570171	VR12
Safety nozzle ( for the blow gun type AM13)	570172	SD12



Series of blow guns for industrial use.

Various accessories can be applied to the type AM13:

AR12 Silenced nozzle lowering noise level (till 63 dB)

AT12 Venturi nozzle, energy saving as thanks to its working principle it aspirates 2/3 of environmental air and in this way allows a wide blow-out effect

VR12 Extension tube

SD12 Safety nozzle forming a protection shield against kicking chips.

Technical data	
Fluid	Compressed air
Pressure range	10 bar
Temperature range	-10 °C ÷ +60 °C
Materials	Body: AH13, in die cast nickel plated aluminium; AN13, AK13, AM13 in acetal resin Seals: Nitrile rubber (NBR) Nozzles: SD12, VR12 in nickel plated brass - AT12, in acetal resin - AR12, in Aluminium