SB SBA

SBF SBOF SFT STP SBL

SUF

SFF

SOF

SOG

SFP

SBP

SGP

SH

SHB

SAO SPA

SPJ SPU

SNP SOP



SBLP Series

Multiple Bellows Suction Cup Special for Soft Packing Bag







FOOD PACKAGING

PLASTIC BAG



Features

- ♦ Large bellows, suitable for handling workpiece for height difference.
- ♦ Good sealing with flat and thin lip.
- ♦ Large flow, handling objects quickly.
- ♦ Silicone material, working temperature range(-40~200°C)

Applications

- ♦ Suitable for handling bags with irregular shapes.
- ♦ Frozen food bags
- ♦ Water bags

Usage

SBLP series suction cup have a large inner space due to the multi bellows design. While handling light and thin workpiece(such as thin plastic bags, paper, etc.), the workpiece usually deforms and it will be sucked into the inner space of suction cup. Therefore, AIRBEST offers an improved solution with a special plug at the bottom to prevent excessive deformation of the workpiece and ensure normal suction.

T1(White round plug): For thin and soft workpiece with large deformation.

T2(Blue flower shape plug):For slightly hard workpiece with small deformation.

How to order

SBLP 30 S - G2M - T2

1







① Serie	es ② Diameter	③ Material & Hardness	4 Connection thread	⑤ Plug
SBLP	30 - φ30mm 40 - φ40mm 50 - φ50mm	S - Silicone 40	Nil - Suction cup alone G2M - G1/4 Male thread G3M - G3/8 Male thread G4M - G1/2 Male thread	Nil - Without plugT1 - Round plug (White)T2 - Flow shape plug (Blue)

Selection

Model/ Connection thread	G2M	G3M	G4M	T1	Т2
SBLP30	•	_	_	\circ	•
SBLP40	_	•	_	•	
SBLP50	_	_	•	\circ	•

 \Diamond Note: "lacktriangle"- standard, in stock. " \bigcirc "-selective,no stock."-"-unavailable.



SBLP Series


Multiple Bellows Suction Cup Special for Soft Packing Bag

Technical parameters

Model	Pull-out force (N)	Inner volume (cm³)	Min. curve radius of workpiece (mm)	Recommended hose dia. (mm)
SBLP30	9	8	17	8
SBLP40	15	14	22	8
SBLP50	25	38	30	10

[♦] Note: Testing vacuum level -60kPa. Workpiece with smooth and clean surface. The data of pull-out force as above are figured out without considering safety factor. The data may be different according to different workpiece surfaces.

Dimensions (mm)



Model/ Size	D	н	h	$L_{\scriptscriptstyle G}$	G	S
SBLP30-G2M	30	36.5	6	9	G1/4	19
SBLP40-G3M	40	40	6	10	G3/8	22
SBLP50-G4M	50	55	6	10	G1/2	28

Mounting parts

Item	Model	Applicable suction cup
Fitting for	PJS-G2M-SBLP30	SBLP30
suction cup	PJS-G3M-SBLP40	SBLP40
	PJS-G4M-SBLP50	SBLP50

 \Diamond Note: Please refer to suction cup with locking fitting and level compensator on page 24.